

**C1500-8, C1500-Q, C1500-G FORMULA WATER-BASE COLOR**Written by Super User. Posted in **MSDS SHEETS****SECTION I - PRODUCT IDENTIFICATION**Product Name: **C1500-8, C1500-Q, C1500-G FORMULA WATER-BASE COLOR**

Revision: 10/22/98

SECTION II - HAZARDOUS INGREDIENTS & OTHER COMPONENTS

INGREDIENT CHEMICAL NAME	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	CAS NUMBER
Triethylamine	N/A	10ppm		121-44-8
N-methyl-2-pyrrolidone	N/A	100ppm		872-50-4
2 Methoxymethylethoxypropanol	100ppm	100ppm		34590-97-8
Ethoxylated C12-14 secondary alcohols	N/A	N/A		84133-50-6

SECTION III - PHYSICAL DATA / CONTENTS WITHOUT PROPELLENT

BOILING POINT: Approx. 212°F	SPECIFIC GRAVITY (H2O=1): N/A
VAPOR PRESSURE (mm Hg): N/A	MELTING POINT: N/A
VAPOR DENSITY (AIR = 1): Heavier than air	EVAPORATION RATE (Butyl Acetate = 1): Slower than ether
SOLUBILITY IN WATER: N/A	APPEARANCE AND ODOR: N/A

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED):	>200°F
FLAMMABLE LIMITS	Combustible Class III
EXTINGUISHING MEDIA:	WATER FOG x STANDARD FOAM x CO ₂ x DRY CHEMICAL x HALON
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Flashback along vapor trail may occur. This material may be ignited by heat, sparks, flame or static electricity.
SPECIAL PRECAUTIONARY STATEMENTS:	N/A

SECTION V: REACTIVITY DATA

STABILITY:	x Stable Unstable
Incompatibility :	Strong mineral acids and oxidizers.
Hazardous Decomposition:	Burning can produce nitrogen oxides, carbon monoxide, and carbon dioxide.
HAZARDOUS POLYMERIZATION:	May Occur xWill not occur
Conditions to Avoid:	Keep product away from heat, sparks, pilot lights, static electricity, and open flame.

SECTION VI: HEALTH HAZARD DATA**ROUTES OF ENTRY & HEALTH HAZARDS (ACUTE AND CHRONIC)**

INGESTION:	May cause chemical burns of the mouth, throat, and esophagus. Signs and symptoms will include pain or discomfort in the mouth, throat, chest, and abdomen, nausea, vomiting, diarrhea, dizziness, and drowsiness, collapse, and coma. In animal studies in rats and mice. NMP was embryotoxic by the oral and intraperitoneal high dose levels which were close to the LD50.
EYES:	Vapor may cause irritation and temporary disturbance of vision. Liquid may produce severe irritation experienced as excess redness and swelling of the conjunctiva with chemical burns of the cornea.
INHALATION:	Exposure above the TLV may cause irritation to the respiratory tract, with sneezing, coughing, burning sensation of the throat constricting sensation of the larynx and difficulty in breathing. High concentrations may cause damage to the liver, kidney, and heart and may cause tracheitis, bronchitis, pneumonitis, and pulmonary edema. Several inhalation studies in rats did not reveal any indication of maternal toxicity or embryotoxicity. In a two year study, NMP did not cause any life-shortening or carcinogenic effects in rats at 0.04 or 0.4 mg/liter (10 and 100ppm respectively).
SKIN:	Prolonged skin contact causes irritation, redness, and defatting of the skin. In a dermal exposure with rats, NMP was only embryotoxic at the high dose level; this effect was attributed to maternal toxicity.

EMERGENCY AND FIRST AID PROCEDURES

INGESTION:	Rinse mouth with water. Give at least 2 glasses of water or milk at once, if the patient is conscious. DO NOT induce vomiting. Seek immediate medical attention.
EYES:	Immediately flush eye with water for at least 15 minutes. The eyelids must be held open and away from the eyeball to ensure that all surfaces are flushed thoroughly. Seek immediate medical attention, preferably an ophthalmologist.
INHALATION:	Remove to fresh air. Give artificial respiration if not breathing. Oxygen may be given if necessary. Call a physician.
SKIN:	

Wash affected area(s) with soap and water. Remove and launder contaminated clothing before reuse. If irritation develops, consult a physician.

SECTION VII: PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE LARGE AMOUNTS ARE RELEASED: Shut off and eliminate all ignition sources. Keep people away. Recover free product. Add sand, earth or other suitable absorbent to spill area. Minimize breathing vapors. Minimize skin contact. Ventilate confined spaces. Open all windows and doors. Keep product out of sewers and watercourses by diking or impounding. Advise authorities if product has entered or may enter sewers, watercourses, or extensive land areas. Assure conformity with applicable governmental regulation. Continue to observe precautions for volatile, flammable vapors from absorbed material.

WASTE DISPOSAL METHOD: Dispose in accordance with local, state, and federal regulation.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep containers tightly closed. Keep containers cool, dry, and away from sources of ignition. Use and store this product with adequate ventilation. Avoid inhalation of vapors and personal contact with the product. Use food personal hygiene practice. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks or other sources of ignition; they may explode and cause injury or death. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

OTHER PRECAUTIONS: Industrial use only.

SECTION VIII: CONTROL MEASURES

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors. If exposure may or does exceed occupational exposure limits use NIOSH approved respirator to prevent overexposure.

VENTILATION: In current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional ventilation or exhaust systems may be required. Where explosive mixtures may be present, systems safe for such location should be used.

LOCAL EXHAUST:

PROTECTIVE GLOVES: The use of gloves impermeable to the specific material handled is advised to prevent skin contact, possible irritation and absorption.

EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

SECTION IX: SPECIAL PRECAUTIONS

HEALTH:	<u>HAZARD RATING KEY</u>
----------------	---------------------------------

FLAMMABILITY:	0 = MINIMAL
REACTIVITY:	1 = SLIGHT
PERSONALPROTECTION:	2 = MODERATE
	3 = SERIOUS
	4 = SEVERE
	* = CHRONIC HEALTH EFFECTS

Disclaimer: The information contained herein is based on the data available to us and is believed to be accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injuries from the use of the product described herein.